

## Data sheet

### SM 022 - Digital output (022-1HB10)

#### Technical data

<b>Order no.</b>	<b>022-1HB10</b>
Type	SM 022 - Digital output
Module ID	0109 AF90
<b>General information</b>	
Note	-
Features	2x DO DC 30 V AC 230 V 3 A Potential separated per channel Relay
<b>Current consumption/power loss</b>	
Current consumption from backplane bus	120 mA
Power loss	0.7 W
<b>Technical data digital outputs</b>	
Number of outputs	2
Cable length, shielded	1000 m
Cable length, unshielded	600 m
Rated load voltage	DC 30 V/ AC 230 V
Permitted range	-
Current consumption from power section supply (without load)	-
Total current per group, horizontal configuration, 40°C	3 A
Total current per group, horizontal configuration, 60°C	3 A
Total current per group, vertical configuration	3 A
Output current at signal "1", rated value	3 A
Signal logic output	Isolated
Output delay of "0" to "1"	10 ms
Output delay of "1" to "0"	5 ms
Minimum load current	-
Lamp load	-
Parallel switching of outputs for redundant control of a load	not possible
Parallel switching of outputs for increased power	not possible
Actuation of digital input	-
Switching frequency with resistive load	max. 0.33 Hz
Switching frequency with inductive load	max. 0.33 Hz
Switching frequency on lamp load	max. 0.33 Hz
Internal limitation of inductive shut-off voltage	-
Short-circuit protection of output	-
Trigger level	-
Number of operating cycle of relay outputs	-
Switching capacity of contacts	3 A
Output data size	2 Bit
<b>Status information, alarms, diagnostics</b>	
Status display	green LED per channel
Interrupts	no

Process alarm	no
Diagnostic interrupt	no
Diagnostic functions	no
Diagnostics information read-out	none
Supply voltage display	green LED
Group error display	red LED
Channel error display	none

## Isolation

Between channels	yes
Between channels of groups to	-
Between channels and backplane bus	yes
Insulation tested with	AC 2200 V

## PWM data

PWM channels	-
PWM time basis	-
Period length	-
Minimum pulse width	-
Type of output	-

## Datasizes

Input bytes	0
Output bytes	1
Parameter bytes	0
Diagnostic bytes	0

## Housing

Material	PPE / PPE GF10
Mounting	Profile rail 35 mm

## Mechanical data

Dimensions (WxHxD)	12.9 mm x 109 mm x 76.5 mm
Net weight	62 g
Weight including accessories	62 g
Gross weight	76 g

## Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

## Certifications

UL certification	yes
KC certification	yes
UKCA certification	yes
ChinaRoHS certification	yes