

## Data sheet

### SM 031 - Analog input (031-1CB70)

#### Technical data

| Order no.  | 031-1CB70                                |
|--|--|
| Type   | SM 031 - Analog input                    |
| Module ID  | 040C 1543                                |
| General information  |  |
| Note   | -  |
| Features   | 2x AI<br>16 Bit<br>Voltage -10 V...+10 V |
| Current consumption/power loss                               |  |
| Current consumption from backplane bus                       | 60 mA                                    |
| Power loss   | 0.8 W                                    |
| Technical data analog inputs                                 |  |
| Number of inputs   | 2  |
| Cable length, shielded                                       | 200 m                                    |
| Rated voltage power section supply                           | DC 24 V                                  |
| Current consumption from power section supply (without load) | 20 mA                                    |
| Voltage inputs   | yes                                      |
| Min. input resistance (voltage range)                        | 200 kOhm                                 |
| Input voltage ranges   | -10 V ... +10 V<br>0 V ... +10 V         |
| Operational limit of voltage ranges                          | +/-0.2%                                  |
| Operational limit of voltage ranges with SFU                 | -  |
| Basic error limit voltage ranges                             | +/-0.1%                                  |
| Basic error limit voltage ranges with SFU                    | -  |
| Destruction limit voltage                                    | max. 30V                                 |
| Current inputs   | -  |
| Max. input resistance (current range)                        | -  |
| Input current ranges   | -  |
| Operational limit of current ranges                          | -  |
| Operational limit of current ranges with SFU                 | -  |
| Basic error limit current ranges                             | -  |
| Radical error limit current ranges with SFU                  | -  |
| Destruction limit current inputs (voltage)                   | -  |
| Destruction limit current inputs (electrical current)        | -  |
| Resistance inputs  | -  |
| Resistance ranges  | -  |
| Operational limit of resistor ranges                         | -  |
| Operational limit of resistor ranges with SFU                | -  |
| Basic error limit  | -  |
| Basic error limit with SFU                                   | -  |
| Destruction limit resistance inputs                          | -  |
| Resistance thermometer inputs                                | -  |
| Resistance thermometer ranges                                | -  |
| Operational limit of resistance thermometer ranges           | -  |

|   |                          |
|---|--------------------------|
| Operational limit of resistance thermometer ranges with SFU | -                        |
| Basic error limit thermoresistor ranges                     | -                        |
| Basic error limit thermoresistor ranges with SFU            | -                        |
| Destruction limit resistance thermometer inputs             | -                        |
| Thermocouple inputs   | -                        |
| Thermocouple ranges   | -                        |
| Operational limit of thermocouple ranges                    | -                        |
| Operational limit of thermocouple ranges with SFU           | -                        |
| Basic error limit thermocouple ranges                       | -                        |
| Basic error limit thermocouple ranges with SFU              | -                        |
| Destruction limit thermocouple inputs                       | -                        |
| Programmable temperature compensation                       | -                        |
| External temperature compensation                           | -                        |
| Internal temperature compensation                           | -                        |
| Temperature error internal compensation                     | -                        |
| Technical unit of temperature measurement                   | -                        |
| Resolution in bit   | 16                       |
| Measurement principle                                       | successive approximation |
| Basic conversion time                                       | 240 µs all channels      |
| Noise suppression for frequency                             | >80dB at 50Hz (UCM<9V)   |

## Status information, alarms, diagnostics

|                                  |                      |
|----------------------------------|----------------------|
| Status display                   | yes                  |
| Interrupts                       | yes, parameterizable |
| Process alarm                    | yes, parameterizable |
| Diagnostic interrupt             | yes, parameterizable |
| Diagnostic functions             | yes                  |
| Diagnostics information read-out | possible             |
| Module state                     | green LED            |
| Module error display             | red LED              |
| Channel error display            | red LED per channel  |

## Isolation

|   |                  |
|---|------------------|
| Between channels  | -                |
| Between channels of groups to                               | -                |
| Between channels and backplane bus                          | yes              |
| Between channels and power supply                           | yes              |
| Max. potential difference between circuits                  | -                |
| Max. potential difference between inputs (Ucm)              | DC 9 V           |
| Max. potential difference between Mana and Mintern (Uiso)   | -                |
| Max. potential difference between inputs and Mana (Ucm)     | DC 1 V           |
| Max. potential difference between inputs and Mintern (Uiso) | DC 75 V/ AC 50 V |
| Max. potential difference between Mintern and outputs       | -                |
| Insulation tested with                                      | DC 500 V         |

## Technical data encoder supply

|                              |   |
|------------------------------|---|
| Number of outputs            | - |
| Output voltage (typ)         | - |
| Output current (rated value) | - |
| Short-circuit protection     | - |
| Binding of potential         | - |

| Datasizes                    |                            |
|------------------------------|----------------------------|
| Input bytes                  | 4                          |
| Output bytes                 | 0                          |
| Parameter bytes              | 20                         |
| Diagnostic bytes             | 20                         |
| Housing                      |                            |
| Material                     | PPE / PPE GF10             |
| Mounting                     | Profile rail 35 mm         |
| Mechanical data              |                            |
| Dimensions (WxHxD)           | 12.9 mm x 109 mm x 76.5 mm |
| Net weight                   | 61 g                       |
| Weight including accessories | 61 g                       |
| Gross weight                 | 75 g                       |
| Environmental conditions     |                            |
| Operating temperature        | 0 °C to 60 °C              |
| Storage temperature          | -25 °C to 70 °C            |
| Certifications               |                            |
| UL certification             | yes                        |
| KC certification             | yes                        |
| UKCA certification           | yes                        |
| ChinaRoHS certification      | yes                        |