

Data sheet

CPU 317PN (317-4PN23)

Technical data

Order no.	317-4PN23
Type	CPU 317PN
General information	
Note	-
Features	Powered by SPEED7 Work memory [KB]: 8MB Integrated: PROFINET IO controller SPEED-Bus Interface [RJ45]: PROFINET Interface [RJ45]: Ethernet PG/OP communication Interface [RS485]: MPI Interface [RS485]: PROFIBUS master/slave, PtP: ASCII, STX/ETX, 3964(R), USS master, Modbus master/slave SD/MMC card slot with locking, up to 32 modules stackable, programmable with WinPLC7, SIMATIC Manager and TIA Portal
SPEED-Bus	yes
Technical data power supply	
Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.4...28.8 V
Reverse polarity protection	yes
Current consumption (no-load operation)	270 mA
Current consumption (rated value)	1.5 A
Inrush current	6 A
I _q	0.28 A²s
Max. current drain at backplane bus	3 A
Max. current drain load supply	-
Power loss	10 W
Load and working memory	
Load memory, integrated	8 MB
Load memory, maximum	8 MB
Work memory, integrated	8 MB
Work memory, maximal	8 MB
Memory divided in 50% program / 50% data	yes
Memory card slot	SD/MMC-Card with max. 2 GB
Hardware configuration	
Racks, max.	4
Modules per rack, max.	8 in multiple-, 32 in a single-rack configuration
Number of integrated DP master	1
Number of DP master via CP	4
Operable function modules	8
Operable communication modules PtP	16
Operable communication modules LAN	8
Status information, alarms, diagnostics	
Status display	yes
Interrupts	no
Process alarm	no

Diagnostic interrupt	no
Diagnostic functions	yes
Diagnostics information read-out	possible
Supply voltage display	green LED
Group error display	red SF LED
Channel error display	none

Command processing times

Bit instructions, min.	0.01 µs
Word instruction, min.	0.01 µs
Double integer arithmetic, min.	0.01 µs
Floating-point arithmetic, min.	0.06 µs

Timers/Counters and their retentive characteristics

Number of S7 counters	2048
S7 counter remanence	adjustable 0 up to 2048
S7 counter remanence adjustable	C0 .. C7
Number of S7 times	2048
S7 times remanence	adjustable 0 up to 2048
S7 times remanence adjustable	not retentive

Data range and retentive characteristic

Number of flags	16384 Byte
Bit memories retentive characteristic adjustable	adjustable 0 up to 16384
Bit memories retentive characteristic preset	MB0 .. MB15
Number of data blocks	8190
Max. data blocks size	64 KB
Number range DBs	1 ... 8190
Max. local data size per execution level	3072 Byte
Max. local data size per block	3072 Byte

Blocks

Number of OBs	24
Maximum OB size	64 KB
Total number DBs, FBs, FCs	-
Number of FBs	8191
Maximum FB size	64 KB
Number range FBs	0 ... 8190
Number of FCs	8191
Maximum FC size	64 KB
Number range FCs	0 ... 8190
Maximum nesting depth per priority class	16
Maximum nesting depth additional within an error OB	4

Time

Real-time clock buffered	yes
Clock buffered period (min.)	6 w
Type of buffering	Vanadium Rechargeable Lithium Battery
Load time for 50% buffering period	20 h
Load time for 100% buffering period	48 h
Accuracy (max. deviation per day)	10 s
Number of operating hours counter	8

Clock synchronization	yes
Synchronization via MPI	Master/Slave
Synchronization via Ethernet (NTP)	Slave

Address areas (I/O)

Input I/O address area	8192 Byte
Output I/O address area	8192 Byte
Process image adjustable	yes
Input process image preset	256 Byte
Output process image preset	256 Byte
Input process image maximal	8192 Byte
Output process image maximal	8192 Byte
Digital inputs	65536
Digital outputs	65536
Digital inputs central	1024
Digital outputs central	1024
Integrated digital inputs	-
Integrated digital outputs	-
Analog inputs	4096
Analog outputs	4096
Analog inputs, central	256
Analog outputs, central	256
Integrated analog inputs	-
Integrated analog outputs	-

Communication functions

PG/OP channel	yes
Global data communication	yes
Number of GD circuits, max.	8
Size of GD packets, max.	22 Byte
S7 basic communication	yes
S7 basic communication, user data per job	76 Byte
S7 communication	yes
S7 communication as server	yes
S7 communication as client	-
S7 communication, user data per job	160 Byte
Number of connections, max.	32

Functionality Sub-D interfaces

Type	X2
Type of interface	RS485
Connector	Sub-D, 9-pin, female
Electrically isolated	yes
MPI	yes
MP2I (MPI/RS232)	-
DP master	-
DP slave	-
Point-to-point interface	-
5V DC Power supply	max. 90mA, isolated
24V DC Power supply	max. 100mA, non-isolated

Type	X3
Type of interface	RS485
Connector	Sub-D, 9-pin, female
Electrically isolated	yes
MPI	-
MP2I (MPI/RS232)	-
DP master	yes
DP slave	yes
Point-to-point interface	yes
5V DC Power supply	max. 90mA, isolated
24V DC Power supply	max. 100mA, non-isolated

Functionality MPI

Number of connections, max.	32
PG/OP channel	yes
Routing	yes
Global data communication	yes
S7 basic communication	yes
S7 communication	yes
S7 communication as server	yes
S7 communication as client	-
Transmission speed, min.	19.2 kbit/s
Transmission speed, max.	12 Mbit/s

Functionality PROFIBUS master

Number of connections, max.	32
PG/OP channel	yes
Routing	yes
S7 basic communication	yes
S7 communication	yes
S7 communication as server	yes
S7 communication as client	-
Activation/deactivation of DP slaves	yes
Direct data exchange (slave-to-slave communication)	-
DPV1	yes
Transmission speed, min.	9.6 kbit/s
Transmission speed, max.	12 Mbit/s
Number of DP slaves, max.	124
Address range inputs, max.	8 KB
Address range outputs, max.	8 KB
User data inputs per slave, max.	244 Byte
User data outputs per slave, max.	244 Byte

Functionality PROFIBUS slave

Number of connections, max.	32
PG/OP channel	yes
Routing	yes
S7 communication	yes
S7 communication as server	yes
S7 communication as client	-
Direct data exchange (slave-to-slave communication)	-

DPV1	yes
Transmission speed, min.	9.6 kbit/s
Transmission speed, max.	12 Mbit/s
Automatic detection of transmission speed	-
Transfer memory inputs, max.	244 Byte
Transfer memory outputs, max.	244 Byte
Address areas, max.	32
User data per address area, max.	32 Byte

Functionality RJ45 interfaces

Type	X5
Type of interface	Ethernet 10/100 MBit
Connector	RJ45
Electrically isolated	yes
PG/OP channel	yes
Number of connections, max.	4
Productive connections	-
Fieldbus	-

Type	X8
Type of interface	Ethernet 10/100 MBit
Connector	RJ45
Electrically isolated	yes
PG/OP channel	yes
Number of connections, max.	8
Productive connections	yes
Fieldbus	-

Point-to-point communication

PtP communication	yes
Interface isolated	yes
RS232 interface	-
RS422 interface	-
RS485 interface	yes
Connector	Sub-D, 9-pin, female
Transmission speed, min.	150 bit/s
Transmission speed, max.	115.5 kbit/s
Cable length, max.	500 m

Point-to-point protocol

ASCII protocol	yes
STX/ETX protocol	yes
3964(R) protocol	yes
RK512 protocol	-
USS master protocol	yes
Modbus master protocol	yes
Modbus slave protocol	-
Special protocols	-

Properties PROFINET I/O controller

Realtime Class	-
Conformance Class	PROFINET IO

Number of PN IO devices	128
IRT support	-
Shared Device supported	-
MRP Client supported	-
Prioritized start-up	-
Number of PN IO lines	1
Address range inputs, max.	4 KB
Address range outputs, max.	4 KB
Transmitting clock	1 ms
Update time	1 ms .. 512 ms
Isochronous mode	-
Parallel operation as controller and I-Device	-

Ethernet communication CP

Number of configurable connections, max.	24
Number of productive connections by Siemens NetPro, max.	14
S7 connections	BSEND, BRCV, GET, PUT, Connection of active and passive data handling
User data per S7 connection, max.	32 KB
TCP-connections	FETCH PASSIV, WRITE PASSIV, Connection of passive data handling
User data per TCP connection, max.	64 KB
ISO-connections	-
User data per ISO connection, max.	-
ISO on TCP connections (RFC 1006)	FETCH PASSIV, WRITE PASSIV, Connection of passive data handling
User data per ISO on TCP connection, max.	32 KB
UDP-connections	-
User data per UDP connection, max.	-
UDP-multicast-connections	-
UDP-broadcast-connections	-

Ethernet open communication

Number of connections, max.	24
ISO on TCP connections (RFC 1006)	TSEND, TRCV, TCON, TDISCON
User data per ISO on TCP connection, max.	8 KB
TCP-Connections native	TSEND, TRCV, TCON, TDISCON
User data per native TCP connection, max.	8 KB
User data per ad hoc TCP connection, max.	1460 Byte
UDP-connections	TUSEND, TURCV
User data per UDP connection, max.	1472 Byte

Management & diagnosis

Protocols	ICMP DCP
Web based diagnosis	-
NCM diagnosis	yes

Housing

Material	PPE
Mounting	Rail System 300

Mechanical data

Dimensions (WxHxD)	80 mm x 125 mm x 120 mm
Net weight	440 g

Weight including accessories	-
Gross weight	-
Environmental conditions	
Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C
Certifications	
UL certification	yes
KC certification	yes