

## Data sheet SM 321 (321-1FH00)

### Technical data

<b>Order no.</b>	<b>321-1FH00</b>
Type	SM 321
<b>General information</b>	
Note	-
Features	16x DI, in groups of 4 AC 120/230 V For 20 pole front connector
SPEED-Bus	-
<b>Current consumption/power loss</b>	
Current consumption from backplane bus	35 mA
Power loss	5 W
<b>Technical data digital inputs</b>	
Number of inputs	16
Cable length, shielded	1000 m
Cable length, unshielded	600 m
Rated load voltage	AC 120/230 V
Current consumption from load voltage L+ (without load)	-
Rated value	AC 120/230 V
Input voltage for signal "0"	AC 0...40 V
Input voltage for signal "1"	AC 79...264 V
Input voltage hysteresis	-
Signal logic input	Sinking input
Frequency range	47...63 Hz
Input resistance	-
Input current for signal "1"	7 mA
Connection of Two-Wire-BEROs possible	yes
Max. permissible BERO quiescent current	1.5 mA
Input delay of "0" to "1"	25 ms
Input delay of "1" to "0"	25 ms
Number of simultaneously utilizable inputs horizontal configuration	16
Number of simultaneously utilizable inputs vertical configuration	16
Input characteristic curve	-
Initial data size	2 Byte
<b>Status information, alarms, diagnostics</b>	
Status display	green LED per channel
Interrupts	no
Process alarm	no
Diagnostic interrupt	no
Diagnostic functions	no
Diagnostics information read-out	none
Supply voltage display	none
Group error display	none

Channel error display none

## Isolation

Between channels yes

Between channels of groups to 4

Between channels and backplane bus yes

Insulation tested with DC 4000 V

## Datasizes

Input bytes 2

Output bytes 0

Parameter bytes 0

Diagnostic bytes 0

## Housing

Material PPE

Mounting Rail System 300

## Mechanical data

Dimensions (WxHxD) 40 mm x 125 mm x 120 mm

Net weight 240 g

Weight including accessories -

Gross weight -

## Environmental conditions

Operating temperature 0 °C to 60 °C

Storage temperature -25 °C to 70 °C

## Certifications

UL certification yes

KC certification -

UKCA certification -

ChinaRoHS certification -