

## Data sheet

IM 060 - Line extension MainDevice (060-1AA01)

### Technical data

<b>Order no.</b>	<b>060-1AA01</b>
Type	IM 060 - Line extension MainDevice
Module ID	8081 8080
<b>General information</b>	
Note	-
Features	Line extension MainDevice Placement at the end of a line Connector: 1x RJ45 plug connector Connection: Cable 950-0KD30, 950-0KD40, 950-0KD50 Max. cable length: 10 m Alternative connection: Ethernet cables with the specification S/STP CAT6a or S/FTP CAT6a Module width 25.8 mm MainDevice 060-1AA01 and SubDevice 061-1BA01 must always be used in pairs
<b>Technical data power supply</b>	
Power supply (rated value)	DC 5 V
Power supply (permitted range)	-
Reverse polarity protection	-
Current consumption (no-load operation)	-
Current consumption (rated value)	40 mA
Inrush current	-
I <sup>2</sup> t	-
Max. current drain at backplane bus	-
Max. current drain load supply	-
Power loss	0.2 W
<b>Status information, alarms, diagnostics</b>	
Status display	yes
Interrupts	no
Process alarm	no
Diagnostic interrupt	no
Diagnostic functions	no
Diagnostics information read-out	none
Supply voltage display	yes
Service Indicator	none
Group error display	yes
Channel error display	none
<b>Hardware configuration</b>	
Racks, max.	5
Modules per rack, max.	total max. 64 minus 2x number line extensions
Number of digital modules, max.	-
Number of analog modules, max.	-
<b>Communication</b>	
Fieldbus	SLIO
Type of interface	-
Connector	RJ45

Topology	-
Electrically isolated	-
Number of participants, max.	-
Node addresses	-
Transmission speed, min.	-
Transmission speed, max.	-
Address range inputs, max.	-
Address range outputs, max.	-
Number of TxPDOs, max.	-
Number of RxPDOs, max.	-

## Housing

Material	PPE / PPE GF10
Mounting	Profile rail 35 mm

## Mechanical data

Dimensions (WxHxD)	25.8 mm x 109 mm x 76.5 mm
Net weight	53 g
Weight including accessories	53 g
Gross weight	68 g

## Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-40 °C to 70 °C

## Certifications

UL certification	yes
KC certification	yes
UKCA certification	yes
ChinaRoHS certification	yes